COMPACT DIELECTRIC OVERBOOTS



| Generation |
|------------|
| |
| |

Power Distribution

Transport

DCOB/R2

An electrically insulating dielectric overboot approved to current European standards, the Respirex dielectric boot provides protection of up to **20kV** over the complete boot for over three minutes.

- · Easy to use front opening & fastening overboot
- Ideal for personnel who have to continually enter and exit hazardous areas
- Yellow dielectric compound shaft
- Single piece injection moulded construction with integral moulded fastener ensures there are no seams or mounting/ fastener holes to leak
- No metal fasteners or components used in the construction
- Kick off lug
- Slip resistant sole in blue dielectric compound
- Fuel and oil resistant shaft and sole
- REACH Compliant

Care

• Machine washable at up to 40°C

• Shelf life of over 10 years

Electrical Protection

Complete boot: 20 kV......3 Minutes, no damage 5 kV.....Less than 5mA Leakage current

Certification

Safety Footwear Electrically Insulating Footwear Dielectric Footwear Personal Protective Equipment EN ISO 20347:2012 I SRC FO EN 50321-1:2018 Class 2 AC ASTM F1117 (20kV) PPE DIR 89/686/EEC

Sizes

| | Medium | Large | Extra-Large |
|----|---------|---------|-------------|
| UK | 6 - 8 | 9 - 11 | 12 - 15 |
| EU | 39 - 42 | 43 - 45 | 46 - 50 |
| US | 7 - 9 | 10 - 12 | 13 - 16 |

