





industry

construction sites

agriculture

potable water

special products

accessories

SYNTHETIC SIGNAL

Fluorescing Fire-Fighting hose

Multi purpose lay flat hose especially for firefighting operations. Outside 100% high tenacity, colour dyed polyester yarn for better visibility. Circular woven twill-weave, warp threads 3-ply twisted for high abrasion resistance. Inner liner made out of a vulcanized high quality EPDM compound.



ADVANTAGES

- Supreme visibility even in smoke filled rooms and in darkness
- · Colour proof
- · Lightweight lay flat hose
- High aging resistance
- Resistance to abrasion
- Cold-resistant up to -40°C
- Heat-resistant up to +100°C
- · Easy maintenance and handling

APPROVALS

- DIN 14811 Class 1 L1
- ÖNORM F 2106

SERVICE

- Standard colours yellow and orange, other colours on request
- Individual marking available
- Binding with international couplings available
 on request
- Other diameters on request
- Available in lengths up to 1000 m depending on diameter

Diameter Inch (mm)	Weight g/m	Burst pressure bar	Working pressure bar	Test pressure bar
1" (25)	130	60	16	24
1 ¼″ (32)	185	60	16	24
1 ½" (38)	200	60	16	24
1 ¾" (45)	235	60	16	24
2" (52)	280	60	16	24
2 ½" (65)	420	60	16	24
2 ¾" (70)	430	60	16	24
3" (75)	480	60	16	24

Changes in technical specification without prior notice